



Canon EOS R6 Mark III + RF 24-105mm F4-7.1 IS STM MILC 32.5 MP CMOS 6960 x 4640 pixels Black

Brand : Canon Product family: EOS Product code: 7084C020

Product name : EOS R6 Mark III + RF 24-105mm F4-7.1 IS STM

- 32.5 megapixel resolution
- 8.5-stop IS
- Up to 7K RAW video
- 40 frames per second
- Wi-Fi** and Bluetooth
- Open Gate
- Dual Pixel CMOS AF II
- CFexpress and UHS-II SD card slots
- RF 24-105mm F4 L IS USM

EOS R6 Mark III + RF 24-105mm F4-7.1 IS STM

Canon EOS R6 Mark III + RF 24-105mm F4-7.1 IS STM. Camera type: MILC, Megapixel (approx.): 32.5 MP, Sensor type: CMOS, Maximum image resolution: 6960 x 4640 pixels. ISO sensitivity (max): 102400. Focal length range: 24 - 105 mm. Fastest camera shutter speed: 1/16000 s. Wi-Fi. Maximum video resolution: 6960 x 3672 pixels. Display diagonal: 7.62 cm (3"), Touchscreen. Viewfinder type: Electronic. Weight: 609 g. Product colour: Black



Picture quality		Viewfinder	
Image sensor aspect ratio	3:2	Viewfinder information	AE lock, AEB, AF method, AF operation, AF point information, Anti-flicker shooting, Aperture, Auto Lighting Optimizer, Battery level, Bluetooth function, Digital Lens Optimizer, Drive mode, Electronic level, Exposure compensation, Exposure level indicator, Exposure simulation, FE lock, FEB, Flash-ready, Focus distance scale, HDR shooting, High-speed sync, Highlight tone priority, Histogram, ISO speed, Image Quality, Maximum burst, Metering mode, Multi-function lock warning, Multiple-exposure shooting, Number of self-timer shooting, Shooting mode, Shutter speed, Still photo cropping, Vertical exposure scale, White balance, Wi-Fi function
Camera type *	MILC		
Megapixel (approx.) *	32.5 MP		
Sensor type *	CMOS		
Sensor cleaning system	EOS integrated		
Maximum image resolution *	6960 x 4640 pixels		
Sensor cleaning system name	EOS Integrated Cleaning System		
Still image resolution(s) *	6960 x 4640, 4800 x 3200, 3472 x 2320, 2400 x 1600, 4320 x 2880, 6160 x 4640, 4256 x 3200, 3072 x 2320, 2112 x 1600, 6960 x 3904, 4800 x 2688, 3472 x 1952, 2400 x 1344, 3200 x 3200, 2320 x 2320, 1600 x 1600		
Supported aspect ratios	1:1, 2:3, 3:2, 3:4, 4:3, 16:9		
Total megapixels	34.2 MP		
Image sensor size (W x H)	35.9 x 23.9 mm		
Built-in low-pass filter	✓	Depth of field preview	✓
Colour filter type	Primary colour filter	Viewfinder resolution (approx.)	3690000 pixels
Sensor shift IS	✓	Ports & interfaces	
Sensor shift IS number of stops (max)	8.5	PictBridge *	✗
Image formats supported *	HEIF, JPEG, Raw	USB version *	3.2 Gen 2 (3.1 Gen 2)
Lens system		USB connector	USB Type-C
Focal length range	24 - 105 mm	HDMI *	✓
Minimum aperture number	40	HDMI connector type	Full-size
Lens structure (elements/groups)	11/13	Microphone in	✓
Number of diaphragm blades	7	Headphone outputs	1
Lens mount interface	Canon RF	Network	
Focusing		Bluetooth *	✓
Focus *	TTL	Bluetooth version	5.1
Focus adjustment *	Auto/Manual	Wi-Fi *	✓
Focusing system	Dual Pixel CMOS AF II	Wi-Fi standards	Wi-Fi 5 (802.11ac)
Auto focusing (AF) modes *	AI Focus, One Shot Focus, Servo Auto Focus		

Focusing		Camera	
Auto Focus (AF) object detection	Bird, Body, CAT, Dog, Eye, Face, Head, Horse, People, Train, Vehicle	White balance *	Cloudy, Custom modes, Daylight, Shade, Tungsten
Face tracking	✓	White balance compensation (Blue/Amber)	±9
Auto Focus (AF) points	4	White balance compensation (Magenta/Green)	±9
Auto Focus (AF) points selection	Auto	Custom white balance	✓
Auto Focus (AF) points manual selection	AF point expansion 4 points, AF point expansion surrounding, Flexible zone AF 1-3	Number of custom white balance settings	4
Auto Focus (AF) lock	✓	Scene modes *	Children, Close-up (macro), Food, Group photo, HDR backlight contro, Handheld night scene, Landscape, Night portrait, Panning, Panorama, Portrait, Silent shutter, Smooth skin, Sports
Auto Focus (AF) assist beam	✓		
Auto Focus (AF) working range	EV -6.5 – 21		
Exposure			
ISO sensitivity (min) *	100		
ISO sensitivity (max) *	102400	Shooting modes *	Intelligent auto, Manual, Scene
Light exposure modes *	Aperture priority AE, Auto, Manual, Shutter priority AE	Self-timer delay *	2,10 s
Light exposure correction *	± 3EV (1/2EV; 1/3EV step)	Playback zoom (max)	10x
Light metering *	Centre-weighted, Evaluative (Multi-pattern), Partial, Spot	Histogram	✓
Auto Exposure (AE) lock	✓	Live view	✓
Number of measurement zones	384	High Dynamic Range (HDR) video processing	✓
Exposure bracketing (AEB)	± 3EV (1/2EV; 1/3EV stop)	HEIF to JPEG conversion	✓
Anti-flicker shooting	✓	Camera drive modes	Continuous high, Continuous high+, Continuous low, Self-timer
Shutter		File numbering options	Auto-reset, Consecutive numbering, Manual reset
Fastest camera shutter speed *	1/16000 s	Number of file naming user presets	2
Slowest camera shutter speed *	30 s	Histogram options	Brightness, RGB
Camera shutter type	Electronic	Highlight alert	✓
Shutter release type	Electromagnetic	Erase options	Select range
Flash		Firmware upgradeable	✓
Flash modes *	Auto, Manual	Tripod mounting supported *	✓
Flash exposure lock	✓	Built-in processor	✓
Flash exposure compensation	✓	Image processor	DIGIC X
Flash exposure correction	±3EV (1/3 EV step)	Windows operating systems supported	Windows 11
Shoe mounting point	✓	Mac operating systems supported	Mac OS X 10.13 High Sierra, Mac OS X 10.14 Mojave, Mac OS X 10.15 Catalina
Shoe mounting point type	Hot shoe		
Flash exposure bracketing	✓		
Video		Design	
Video recording *	✓	Market segment *	Professional
Maximum video resolution *	6960 x 3672 pixels	Product colour *	Black
Video resolutions	1920 x 1080,2048 x 1080,3840 x 2160,4096 x 2160	Dustproof	✓
Video formats supported	H.265, MP4	Waterproof	✓
Dual card video recording	✓	Material	Magnesium
Colour sampling	YCbCr4:2:0 8-bit, YCbCr4:2:2 10-bit	Battery	
Audio		Battery technology *	Lithium-Ion (Li-Ion)
Built-in microphone *	✓	Battery life (display)	620 shots
Built-in speaker(s)	✓	Battery life (viewfinder)	390 shots
Memory		Battery type	LP-E6P
Compatible memory cards *	CFexpress 2.0 Type B, SD, SDHC, SDXC	Battery level indicator	✓
Memory slots	2	Battery level indicator number of levels	6
Maximum memory card size	8 TB	Power	
Display		USB Type-C charging port *	✓
		Operational conditions	
Display *	LCD	Operating temperature (T-T)	0 - 40 °C
Touchscreen *	✓	Weight & dimensions	
Display diagonal *	7.62 cm (3")	Width	138.4 mm
Display resolution	160000 dot		

Display		Weight & dimensions	
Viewing angle, horizontal	170°	Depth	88.4 mm
Viewing angle, vertical	170°	Height	98.4 mm
Anti-smudge coating	✓	Weight	609 g
Display brightness adjustment	✓	Packaging data	
Number of manual brightness adjustment levels	4	Quantity per pack	1 pc(s)
Viewfinder		Package width	225 mm
Viewfinder type	Electronic	Package depth	282 mm
Magnification	0.76x	Package height	188 mm
Viewfinder screen size	0.5"	Package weight	2.03 kg
Viewfinder eyepoint (approx.)	2.3 cm	Packaging content	
Viewfinder frame rate (smooth mode)	120 fps	Hand strap	✓
		Power cord included	✓
		AC adapter included *	✓
		Battery charger included	✓
		Batteries included	✓
		Lens cap included	✓
		Logistics data	
		Pallet gross length	120 cm
		Pallet gross width	80 cm
		Pallet gross height	110.5 cm
		Products per pallet layer	18 pc(s)
		Pallet gross weight	141.7 kg
		Layers per pallet	3 pc(s)
		Products per pallet	54 pc(s)
		Master (outer) case width	246 mm
		Master (outer) case length	588 mm
		Master (outer) case height	325 mm
		Master (outer) case gross weight	7.04 kg
		Products per master (outer) case	3 pc(s)



4549292246407

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.