

iivama ProLite XB2793HSU-B1 computer monitor 68.6 cm (27") 1920 x 1080 pixels Full HD LED Black

Brand : iivama

Product family: ProLite

Product code: XB2793HSU-B1

Product name : XB2793HSU-B1

Eco-conscious 27" IPS monitor with ergonomic stand for modern workplaces

iivama ProLite XB2793HSU-B1. Display diagonal: 68.6 cm (27"), Display resolution: 1920 x 1080 pixels, HD type: Full HD, Display technology: LED, Display surface: Matt, Response time: 1 ms, Native aspect ratio: 16:9, Viewing angle, horizontal: 178°, Viewing angle, vertical: 178°. Built-in speaker(s). Built-in USB hub, USB hub version: 2.0. VESA mounting, Height adjustment. Product colour: Black



Display		Ergonomics	
Display diagonal *	68.6 cm (27")	Cable lock slot type	Kensington
Display resolution *	1920 x 1080 pixels	Height adjustment *	✓
HD type *	Full HD	Adjustable height (max)	15 cm
Native aspect ratio *	16:9	Pivot	✓
Display technology *	LED	Pivot angle	0 - 90°
Panel type *	IPS	Swivelling	✓
Touchscreen *	✗	Swivel angle range	-60 - 60°
Display brightness (typical)	350 cd/m²	Tilt adjustment	✓
Response time *	1 ms	Tilt angle range	5 - 23°
Response time (MPRT)	1 ms	On Screen Display (OSD)	✓
Display surface	Matt	On Screen Display (OSD) languages	Czech, German, English, Spanish, French, Italian, Japanese, Dutch, Polish, Russian, Ukrainian
Screen shape *	Flat		
Contrast ratio (typical) *	1500:1		
Contrast ratio (dynamic)	80000000:1		
Maximum refresh rate *	120 Hz		
Viewing angle, horizontal	178°		
Viewing angle, vertical	178°		
Display number of colours *	16.7 million colours		
Pixel pitch	0.311 x 0.311 mm		
Horizontal scan range	30 - 140 kHz		
Viewable size, horizontal	59.8 cm		
Viewable size, vertical	33.6 cm		
Display diagonal (metric)	68.6 cm		
Colour gamut standard	NTSC, sRGB		
sRGB coverage (typical)	96%		
NTSC coverage (typical)	72%		
Performance		Power	
AMD FreeSync *	✓	Energy efficiency class (SDR) *	C
VESA Adaptive Sync support	✓	Energy efficiency class (HDR) *	Not available
Flicker-free technology	✓	Energy consumption (SDR) per 1000 hours *	14.1 kWh
		Power consumption (typical) *	14 W
		Power consumption (standby) *	0.5 W
		Power consumption (off)	0.3 W
		AC input voltage	100 - 250 V
		AC input frequency	50/60 Hz
		Power supply type	Internal
		Energy efficiency scale	A to G
		Weight & dimensions	
		Width (with stand)	611.5 mm
		Depth (with stand)	224.5 mm
		Height (with stand)	547.5 mm
		Weight (with stand)	6 kg

Performance		Weight & dimensions	
Low Blue Light technology	✓	Width (without stand)	611.5 mm
Multimedia		Depth (without stand)	224.5 mm
Number of speakers	2	Height (without stand)	404 mm
RMS rated power	4 W	Packaging data	
Built-in speaker(s) *	✓	Package width	691 mm
Design		Package depth	142 mm
Market positioning *	Business	Package height	442 mm
Product colour *	Black	Package weight	7.8 kg
Ports & interfaces		USB cable length	1.5 m
Built-in USB hub *	✓	Packaging content	
USB hub version	2.0	Cables included	AC, USB, HDMI
Number of downstream ports	2	HDMI cable length	1.5 m
HDMI *	✓	Power cable length	1.8 m
HDMI ports quantity	1	Sustainability	
HDMI version	1.4	Sustainability certificates	ErP, TCO
DisplayPorts quantity	1	Other features	
DisplayPort version	1.2	User controls	picture adjust (brightness, contrast, ECO, ACR, OD, motion blur reduction, Adaptive Sync), colour settings (i-Style colour, blue light reducer, RGB range, colour temperature, user preset), OSD (OSD H. position, OSD V. position, OSD rotate, OSD time, OSD background, DDC/CI control, display information), language, extra1 (sharpness, video mode adjust, opening logo, power LED), extra 2 (shortcut key, FW version), input select, audio settings (volume, mute audio), reset (reset all)
Headphone out *	✓		
HDCP	✓		
Ergonomics			
VESA mounting *	✓		
Panel mounting interface	100 x 100 mm	Packaging content	quick start guide, safety guide
Wall mountable	✓	Weight	6 kg
Cable management	✓	Width	611.5 mm
Cable lock slot *	✓	Depth	224.5 mm
		Control panel	Joystick: Centre: Power/Menu, Up/Signal Select, Down, Left/Submenu, Right/Volume
		Compliance certificates	CE, EAC, PSE, REACH, RoHS, TÜV mark, UKCA, VCCI, WEEE
Technical details			
		Native refresh rate	60 Hz



4948570126705

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.