



Spade Dock 4038

7-in-1 DockingStation with LCD-Display and PD 100 W

Article no. 61216 EAN code 4250078175544

Model designation
IB-DK4038-LCD

Spade Dock 4038 is made for people who work wherever the day takes them. It brings together the connections you actually need and leaves out everything you do not. Whether you are setting up at a hotel desk, a meeting room, or your kitchen table: this DockingStation turns a notebook into a capable workspace in seconds. Spade Dock 4038 proves that working away from home can still feel organized, practical, and surprisingly comfortable.



Host

Supports USB 3.2
Gen 2 Type-C®



Video output

HDMI® 4K@60 Hz



Power Delivery

USB Type-C® PD 3.0
up to 100 watts



USB ports

USB Type-A, 480 Mbps / 10 Gbps
USB Type-C®, 10 Gbps



LAN Port

RJ45 Gigabit Ethernet


FRONT VIEW



REAR VIEW



SIDE VIEW



KEY FEATURES



Infotainment

The built-in LCD display informs you at a glance about the dock's connection status. A single press of the button cycles through the information of each port. A double press rotates the display by 90 degrees, allowing comfortable viewing from different positions.



Your 7-in-1 everyday tool

Spade Dock 4038 brings the essential connections together in one compact DockingStation. With HDMI®, USB, Ethernet, and charging support, it expands your notebook into a capable workstation in seconds. Every port has a purpose, don't pay for unnecessary features.



4K 4 you

The HDMI® port supports resolutions up to 4K at 60 Hz. Connect an external monitor and expand your workspace with sharp and smooth visuals: ideal for presentations, creative work, or simply having more room for multitasking. One cable instantly transforms your notebook into a larger workstation.

PACKING CONTENT

- ▶ 1x Spade Dock 4038
- ▶ 1x Manual

PRODUCT FEATURES

Color	Material	ON/OFF button	Cable length	LED	Video technology	Power supply
Black	Aluminum	No	Integrated USB Type-C® cable, 25 cm	Display	HDMI®	No power adapter

INTERFACE TO HOST COMPUTER

Plug	Position	Version & transfer rate	Features
USB Type-C®	Side	USB 3.2 Gen 2 (10 Gbps)	Built-in host cable

USB CONNECTIONS

Port	Position	Version & Transferrate
1x USB Type-A	Front	USB 2.0 (480 Mbps)
2x USB Type-A	Front	USB 3.2 Gen 2 (10 Gbps)
1x USB Type-C®	Front	USB 3.2 Gen 2 (10 Gbps)
1x USC Type-C®	Rear	Power Delivery 3.0 Upstream up to 100 watts

VIDEO CONNECTION AND DISPLAY OUTPUT MATRIX

Video matrix overview, maximum resolution		
Number of monitors	Connection (plug-in)	Output
	HDMI®	HDMI®
Single video output	✓	4K@60 Hz

FURTHER IN-/OUTPUTS

Port	Position	Features
1x HDMI®	Rear	HDMI® 2.0, max. resolution up to 4K@60 Hz
LAN RJ45 Gigabit Ethernet	Side	10/100/1000 Mbps

SYSTEM REQUIREMENTS

Supported operating systems	Requirements and features	Video compatibility
Windows®, macOS®, ChromeOS™, Linux®	One free USB Type-C® port on your host computer	Supports one monitor via HDMI® connection

NEW USB NOMENCLATURE

Legacy USB standards	Current USB standards	Data transfer rate
USB 3.0 = USB 3.1 (Gen 1)	= USB 3.2 Gen 1	= 5 Gbps
USB 3.1 = USB 3.1 (Gen 2)	= USB 3.2 Gen 2	= 10 Gbps
USB 3.2 (Gen 2x2)	= USB 3.2 Gen 2x2	= 20 Gbps
	= USB4® Gen 2x1	= 10 Gbps
	= USB4® Gen 2x2	= 20 Gbps
	= USB4® Gen 3x2	= 40 Gbps

LOGISTICAL DATA

Packing unit	Total weight	Gross weight (with packing)	Net weight	Dimension/ carton	Dimension with packing	Dimension of article	Country of origin
60 pcs./carton	9.78 kg	0.150 kg	0.054 kg	425x393x235 mm	20x100x200 mm	40x120x15 mm	China

The terms HDMI® and HDMI® High-Definition Multimedia Interface, and the HDMI® logo are trademarks or registered trademarks of HDMI® LA, Inc. in the United States and other countries.

Apple and macOS, MAC, iTunes and Macintosh are registered trademarks of Apple Computer Inc.

Microsoft, Windows and the Windows logo are registered trademarks of Microsoft Corporation.

USB Type-C® and USB-C® are registered trademarks of USB Implementers Forum.

All other trademarks and brand names are the property of their respective owners.

Chrome OS is a trademark of Google Inc. Use of this trademark is subject to Google Permissions.

For support, please contact us at support@raidsonic.de
For orders, please contact us at info@raidsonic.de