



# Lindy 70617 audio converter Black

Brand : Lindy

Product code: 70617

Product name : 70617

- Provides 2 channel recording and playback, allowing USB-C devices to exchange high quality audio with Dante® networks in professional AV, broadcast, conferencing and installed audio workflows
  - Supports 44.1/48kHz sampling rates for accurate, reliable audio reproduction across live sound, meeting room, studio and commercial AV applications
  - Class compliant plug and play design enables quick setup with Windows, macOS, iOS and Android devices without the need for additional drivers
  - Compact metal housing with USB or 802.3af PoE power support, making it suitable for field use, desktop setups, AV racks and fixed installations
- USB-C Dante In/Out Converter
- Lindy 70617. USB connector type: USB Type-C. Power consumption (max): 9 W, Operating voltage: 5 V. Width: 114 mm, Depth: 48 mm, Height: 26 mm. Cables included: USB Type-A to USB Type-C, USB Type-C to USB Type-C, Package weight: 260 g, Package type: Box



| Inputs                     |                                                                | Power                       |                                                    |
|----------------------------|----------------------------------------------------------------|-----------------------------|----------------------------------------------------|
| USB connector type         | USB Type-C                                                     | Operating voltage           | 5 V                                                |
| Outputs                    |                                                                | Weight & dimensions         |                                                    |
| RJ-45 ports quantity       | 1                                                              | Width                       | 114 mm                                             |
| Technical details          |                                                                | Depth                       | 48 mm                                              |
| USB version                | 2.0                                                            | Height                      | 26 mm                                              |
| Maximum transfer distance  | 100 m                                                          | Weight                      | 190 g                                              |
| Maximum data transfer rate | 100 Mbit/s                                                     | Operational conditions      |                                                    |
| Product colour             | Black                                                          | Operating temperature (T-T) | -5 - 55 °C                                         |
| Housing material           | Metal                                                          | Storage temperature (T-T)   | -25 - 70 °C                                        |
| Warranty period            | 3 year(s)                                                      | Packaging data              |                                                    |
| Compliance certificates    | CE, UKCA, Federal Communications Commission (FCC), REACH, RoHS | Quantity                    | 1                                                  |
| Power over Ethernet (PoE)  | ✓                                                              | Cables included             | USB Type-A to USB Type-C, USB Type-C to USB Type-C |
| Power                      |                                                                | Manual                      | ✓                                                  |
| Power consumption (max)    | 9 W                                                            | Package weight              | 260 g                                              |
|                            |                                                                | Package type                | Box                                                |



4002888706179

### Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.