

ZYXEL

Zyxel GS1200-5HP v2 Managed Gigabit Ethernet (10/100/1000)  
Power over Ethernet (PoE) Grey

Brand : Zyxel

Product code: GS1200-5HPV2-EU0101F

Product name : GS1200-5HP v2



GS1200-5HP v2 - 5-Port Web Managed PoE Gigabit Switch  
Zyxel GS1200-5HP v2. Switch type: Managed. Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000), Basic switching RJ-45 Ethernet ports quantity: 5. Full duplex. MAC address table: 2000 entries, Switching capacity: 10 Gbit/s. Networking standards: IEEE 802.3ab, IEEE 802.3af, IEEE 802.3at, IEEE 802.3az, IEEE 802.3p, IEEE 802.3u, IEEE 802.3x,.... Power over Ethernet (PoE)

| Management features                             |                                                                                                            | Design                                         |                  |
|-------------------------------------------------|------------------------------------------------------------------------------------------------------------|------------------------------------------------|------------------|
| Switch type *                                   | Managed                                                                                                    | Reset button                                   | ✓                |
| Quality of Service (QoS) support                | ✓                                                                                                          | LED indicators                                 | Link, PoE, Power |
| Web-based management                            | ✓                                                                                                          | On/off switch                                  | ✓                |
| Ports & interfaces                              |                                                                                                            | Safety                                         | LVD EN60950-1    |
| Basic switching RJ-45 Ethernet ports quantity * | 5                                                                                                          | Performance                                    |                  |
| Basic switching RJ-45 Ethernet ports type *     | Gigabit Ethernet (10/100/1000)                                                                             | Firmware upgradeable                           | ✓                |
| Network                                         |                                                                                                            | Power                                          |                  |
| Networking standards *                          | IEEE 802.3ab, IEEE 802.3af, IEEE 802.3at, IEEE 802.3az, IEEE 802.3p, IEEE 802.3u, IEEE 802.3x, IEEE 802.3z | Output current                                 | 1.3 A            |
| 10G support *                                   | ✗                                                                                                          | Power consumption (max)                        | 72 W             |
| Port mirroring                                  | ✓                                                                                                          | Power over Ethernet (PoE)                      |                  |
| Full duplex                                     | ✓                                                                                                          | Power over Ethernet (PoE) *                    | ✓                |
| Flow control support                            | ✓                                                                                                          | Power over Ethernet (PoE) ports quantity       | 5                |
| Link aggregation                                | ✓                                                                                                          | Power over Ethernet plus (PoE+) ports quantity | 4                |
| Broadcast storm control                         | ✓                                                                                                          | Total Power over Ethernet (PoE) budget         | 60 W             |
| Auto MDI/MDI-X                                  | ✓                                                                                                          | Operational conditions                         |                  |
| VLAN support                                    | ✓                                                                                                          | Operating temperature (T-T)                    | 0 - 40 °C        |
| Virtual LAN features                            | Port-based VLAN                                                                                            | Storage temperature (T-T)                      | -40 - 70 °C      |
| Data transmission                               |                                                                                                            | Operating relative humidity (H-H)              | 10 - 90%         |
| Switching capacity *                            | 10 Gbit/s                                                                                                  | Storage relative humidity (H-H)                | 10 - 90%         |
| MAC address table *                             | 2000 entries                                                                                               | Weight & dimensions                            |                  |
| Store-and-forward                               | ✓                                                                                                          | Width                                          | 193 mm           |
| Jumbo frames support                            | ✓                                                                                                          | Depth                                          | 84 mm            |
|                                                 |                                                                                                            | Height                                         | 26 mm            |
|                                                 |                                                                                                            | Weight                                         | 392 g            |

| Data transmission                   |             | Packaging data              |                          |
|-------------------------------------|-------------|-----------------------------|--------------------------|
| Jumbo frames                        | 9000        | Package type                | Box                      |
| Packet buffer memory                | 0.1 MB      | Package width               | 210 mm                   |
| Security                            |             | Package depth               | 132 mm                   |
| DHCP features                       | DHCP client | Package height              | 78 mm                    |
| IGMP snooping                       | ✓           | Package weight              | 950 g                    |
| Multicast features                  |             | Certificates                |                          |
| Multicast support                   | ✓           | Certification               | CE, FCC, C-Tick, Class A |
| Number of multicast groups filtered | 20          | Logistics data              |                          |
| Design                              |             | Harmonized System (HS) code | 85176990                 |
| Rack mounting *                     | ✗           |                             |                          |
| Stackable *                         | ✗           |                             |                          |
| Product colour                      | Grey        |                             |                          |



4718937598717

### Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.