

NETGEAR GS316EPP Управляемый Gigabit Ethernet (10/100/1000)
Питание по Ethernet (PoE) Черный



Производитель : NETGEAR

Код товара: GS316EPP-100PES

Модель : GS316EPP

NETGEAR GS316EPP. Тип свича: Управляемый. Тип RJ-45 Ethernet портов для основного подключения: Gigabit Ethernet (10/100/1000), Количество RJ-45 Ethernet портов для основного подключения: 16. Полнодуплексный режим. Размер адресной таблицы: 4000 записей, Коммутационная способность: 28 Gbit/s. Стандарты сети: IEEE 802.3, IEEE 802.3ab, IEEE 802.3af, IEEE 802.3at, IEEE 802.3u, IEEE 802.3x. Питание по Ethernet (PoE)

Характеристики управления		Характеристики многоадресной передачи	
Тип свича *	Управляемый	Поддержка многоадресной передачи	✓
Поддержка Quality of Service (QoS)	✓	Дизайн	
Управление через веб-интерфейс	✓	Составной *	✗
Порты и интерфейсы		Цвет товара	Черный
Количество RJ-45 Ethernet портов для основного подключения *	16	Светодиодные индикаторы	✓
Тип RJ-45 Ethernet портов для основного подключения *	Gigabit Ethernet (10/100/1000)	Энергопитание	
Количество портов Gigabit Ethernet (медные)	16	Источник питания *	Постоянный ток
Количество слотов для SFP модулей	1	Блок питания в комплекте *	✓
Сеть		Power over Ethernet (PoE)	
Стандарты сети *	IEEE 802.3, IEEE 802.3ab, IEEE 802.3af, IEEE 802.3at, IEEE 802.3u, IEEE 802.3x	Питание по Ethernet (PoE) *	✓
Полнодуплексный режим	✓	Количество портов PoE	15
Поддержка управления потоками	✓	Общий объем Power over Ethernet (PoE)	231 W
Объединение каналов	✓	Условия эксплуатации	
Контроль "широковещательного шторма"	✓	Диапазон температур при эксплуатации	0 - 40 °C
Поддержка VLAN	✓	Диапазон температур при хранении	-20 - 70 °C
Передача данных		Диапазон относительной влажности при эксплуатации	0 - 90%
Коммутационная способность *	28 Gbit/s	Диапазон относительной влажности при хранении	0 - 95%
Размер адресной таблицы *	4000 записей	Рабочая высота	0 - 3000 m
Поддержка Jumbo Frames	✓	Высота в нерабочем режиме	0 - 3000 m
джамбо кадры	10000	Вес и размеры	
Безопасность		Ширина	286 mm
Функции DHCP	DHCP client	Глубина	102 mm
Список контроля доступа (ACL)	✓	Высота	27 mm
		Вес	883 g
		Логистические данные	
		Код гармонизированной системы описания (HS)	85176990



0606449154405



606449154405



5715063041086

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.