

## Chieftec Stealth 1000W Vega M Series SPX-1000-FC 80+ Platin power supply unit 24-pin ATX ATX Black

**Brand :** Chieftec

**Product family:** Stealth

**Product code:** SPX-1000-FC

**Product name :** 1000W Vega M Series SPX-1000-FC 80+ Platin

Chieftec Stealth 1000W Vega M Series SPX-1000-FC 80+ Platin. Total power: 1000 W, AC input voltage: 100 - 240 V, AC input frequency: 50/60 Hz. Motherboard power connector: 24-pin ATX, Motherboard power cable length: 60 cm, SATA power cable length: 150,500 mm. Purpose: PC, Power supply unit (PSU) form factor: ATX, 80 PLUS certification: 80 PLUS Platinum. Product colour: Black, Cooling type: Active, Fan diameter: 13.5 cm. Width: 150 mm, Depth: 140 mm, Height: 86 mm



| Power                                         |                                                                                      | Ports & interfaces                     |                  |
|-----------------------------------------------|--------------------------------------------------------------------------------------|----------------------------------------|------------------|
| Total power *                                 | 1000 W                                                                               | EPS power connector (8-pin)            | ✓                |
| AC input voltage *                            | 100 - 240 V                                                                          | EPS power connector (4+4 pin)          | ✓                |
| AC input frequency                            | 50/60 Hz                                                                             | PCI Express power connectors (6+2 pin) | 3                |
| Input current                                 | 13.0-6.5 A                                                                           | PCI Express power cable length         | 65 cm            |
| Power Factor Correction (PFC) type            | Active                                                                               | PCI Express connector                  | ✓                |
| Combined power (+3.3V)                        | 100 W                                                                                | Number of EPS connectors               | 1                |
| Combined power (+12V)                         | 1000 W                                                                               | Cabling type                           | Fully-Modular    |
| Combined power (+5Vsb)                        | 15 W                                                                                 | Performance                            |                  |
| Max output current (+3.3V)                    | 20 A                                                                                 | 80 PLUS certification *                | 80 PLUS Platinum |
| Max output current (+12V)                     | 83.3 A                                                                               | Purpose *                              | PC               |
| Max output current (+5V)                      | 20 A                                                                                 | Power supply unit (PSU) form factor *  | ATX              |
| Max output current (+5Vsb)                    | 3 A                                                                                  | ATX version                            | 3.1              |
| Power protection features                     | Over current, Over voltage, Overload, Short circuit, Surge and inrush, Under voltage | Bearing technology                     | FDB              |
| Ports & interfaces                            |                                                                                      | Design                                 |                  |
| Motherboard power connector *                 | 24-pin ATX                                                                           | Product colour                         | Black            |
| Motherboard power cable length                | 60 cm                                                                                | Cooling type                           | Active           |
| Number of SATA power connectors               | 8                                                                                    | Fan diameter                           | 13.5 cm          |
| SATA power cable length                       | 150,500 mm                                                                           | Weight & dimensions                    |                  |
| Number of SATA power cables                   | 3                                                                                    | Width                                  | 150 mm           |
| Peripheral (Molex) power connectors (4-pin) * | 1                                                                                    | Depth                                  | 140 mm           |
| Peripheral (Molex) power cable length         | 150,500 mm                                                                           | Height                                 | 86 mm            |
|                                               |                                                                                      | Packaging data                         |                  |
|                                               |                                                                                      | Package type                           | Box              |



0753263079251



753263079251

### Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.