



Dahua Technology Intelligent EV Charger

Brand : Dahua Technology

Product code: DHI-ICS-A220E-B2D-Z

Product name : Intelligent EV Charger

- 4.3-inch LCD display
- 3 charging methods: Free vending (plug&play), RFID control, and app control
- Supports OCPP 1.6j
- Working temperature: -30 °C to +50 °C (- 22 °F to +122 °F)
- Integral 30 mA Type A and DC 6mA RCD function protection, and supports PEN protection
- IP55 and IK10 rated

22 kW, 400 VAC, 50/60 Hz, 32 A, OCPP1.6j, 4.3", Wi-Fi, 4G or Ethernet, Bluetooth, Black

Dahua Technology Intelligent EV Charger. Product colour: Black, Mounting type: Wall, Housing material: Polycarbonate (PC). Open Charge Point Protocol (OCPP) version: 1.6j, Socket type: Type 2, Power protection features: Over voltage, Under voltage, Short circuit, Overheating, Over current. Power source type: AC, Nominal voltage: 400 V, Maximum charging power: 22000 W. Width: 273 mm, Depth: 171.5 mm, Height: 443 mm

Design		Power	
Product colour *	Black	Nominal frequency	50 Hz
Housing material *	Polycarbonate (PC)	Maximum operating power (three-phase)	22 kW
Mounting type *	Wall	Number of phases *	3
Built-in display *	✓	Maximum operating current (three-phase)	32 A
Display diagonal	10.9 cm (4.3")	Ports & interfaces	
LED indicators	Charging, Fault, Status	Wi-Fi	✓
Features		Ethernet LAN	✓
Open Charge Point Protocol (OCPP) version	1.6j	Operational conditions	
Bluetooth	✓	Operating temperature (T-T)	-30 - 50 °C
Sockets quantity	1	Storage temperature (T-T)	-40 - 70 °C
Socket type	Type 2	Operating relative humidity (H-H)	5 - 95%
RFID reader	✓	Operating altitude	0 - 2000 m
Power protection features	Over voltage, Under voltage, Short circuit, Overheating, Over current	Technical details	
Mechanical impact protection code	IK10	Doesn't contain	Lead, Mercury, Cadmium
International Protection (IP) code	IP55	Compliance certificates	RoHS
Quantity per pack	1 pc(s)	Weight & dimensions	
Certification	IEC 61851-1, IEC 62196-2	Width	273 mm
Power		Depth	171.5 mm
Power source type *	AC	Height	443 mm
Nominal voltage	400 V	Weight	6 kg
Maximum charging power	22000 W	Package width	423 mm
Three-phase output voltage supported	400 V	Package depth	606 mm
		Package height	409 mm
		Package weight	12 kg



6939554905414

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.