



## APC Smart-UPS, Line Interactive, 2200VA, Rackmount 2U, 230V, 8x IEC C13+2x IEC C19 outlets, Network Card, AVR, LCD



**Brand :** APC

**Product code:** SMT2200RMI2UNC

**Product name :** Smart-UPS, Line Interactive, 2200VA, Rackmount 2U, 230V, 8x IEC C13+2x IEC C19 outlets, Network Card, AVR, LCD

Smart-UPS, Line Interactive, 2200VA, Rackmount 2U, 230V, 8x IEC C13+2x IEC C19 outlets, Network Card, AVR, LCD

APC Smart-UPS, Line Interactive, 2200VA, Rackmount 2U, 230V, 8x IEC C13+2x IEC C19 outlets, Network Card, AVR, LCD. UPS topology: Line-Interactive, Output power capacity: 2.2 kVA, Output power: 1980 W. AC outlet types: C13 coupler, C19 coupler, AC outlets quantity: 9 AC outlet(s). Battery technology: Sealed Lead Acid (VRLA), Battery capacity: 509 Ah, Battery recharge time: 5 h. Form factor: Rackmount, Product colour: Black, Rack capacity: 2U. Compliance certificates: RoHS, Certification: CE, EAC, EN/IEC 62040-1, EN/IEC 62040-2, GS Mark, IRAM, RCM, VDE, WEEE

| Features                        |                          | Design                            |                                                                        |
|---------------------------------|--------------------------|-----------------------------------|------------------------------------------------------------------------|
| UPS topology *                  | Line-Interactive         | Product colour *                  | Black                                                                  |
| Output power capacity *         | 2.2 kVA                  | Display type                      | LCD                                                                    |
| Output power *                  | 1980 W                   | LED indicators                    | ✓                                                                      |
| Waveform *                      | Sine                     | <b>Operational conditions</b>     |                                                                        |
| Input operation voltage (min) * | 151 V                    | Operating temperature (T-T)       | 0 - 40 °C                                                              |
| Input operation voltage (max) * | 302 V                    | Storage temperature (T-T)         | -15 - 45 °C                                                            |
| Input frequency *               | 50/60 Hz                 | Operating relative humidity (H-H) | 0 - 95%                                                                |
| Output operation voltage (min)  | 220 V                    | Storage relative humidity (H-H)   | 0 - 95%                                                                |
| Output operation voltage (max)  | 240 V                    | Operating altitude                | 0 - 3000 m                                                             |
| Output frequency                | 50/60 Hz                 | Non-operating altitude            | 0 - 15000 m                                                            |
| Surge energy rating             | 375 J                    | <b>Certificates</b>               |                                                                        |
| Response time                   | 4 ms                     | Compliance certificates           | RoHS                                                                   |
| Emergency Power Off (EPO)       | 0                        | Certification                     | CE, EAC, EN/IEC 62040-1, EN/IEC 62040-2, GS Mark, IRAM, RCM, VDE, WEEE |
| Noise level                     | 55 dB                    | <b>Packaging content</b>          |                                                                        |
| Surge protection                | ✓                        | Rack mount kit                    | ✓                                                                      |
| Audible alarm(s)                | ✓                        | Cables included                   | Input power cable, USB cable                                           |
| Web-based management            | ✓                        | Management card included          | ✓                                                                      |
| Audible alarm modes             | Battery replacement      | Quick installation guide          | ✓                                                                      |
| Auto-restart                    | ✓                        | <b>Sustainability</b>             |                                                                        |
| <b>Ports &amp; interfaces</b>   |                          | Sustainability certificates       | Green Premium                                                          |
| AC outlet types                 | C13 coupler, C19 coupler | <b>Weight &amp; dimensions</b>    |                                                                        |
| AC outlets quantity             | 9 AC outlet(s)           | Width                             | 480 mm                                                                 |
| Number of output IEC jumpers    | 3                        | Depth                             | 683 mm                                                                 |
| USB 2.0 ports quantity          | 1                        | Height                            | 86 mm                                                                  |
| Ethernet LAN (RJ-45) ports      | 1                        | Weight                            | 42.2 kg                                                                |
| SmartSlot                       | ✓                        | <b>Packaging data</b>             |                                                                        |
| SmartConnect port               | ✗                        | Resource CD                       | ✓                                                                      |
| <b>Battery</b>                  |                          | Package width                     | 600 mm                                                                 |
| Battery technology              | Sealed Lead Acid (VRLA)  | Package depth                     | 980 mm                                                                 |
| Battery capacity                | 509 Ah                   | Package height                    | 254 mm                                                                 |
| Battery recharge time           | 5 h                      | Package weight                    | 49.6 kg                                                                |
| Hot-swap battery                | ✓                        | <b>Logistics data</b>             |                                                                        |
| Automatic battery test          | ✓                        | Products per pallet               | 8 pc(s)                                                                |
| Cold start                      | ✓                        | Harmonized System (HS) code       | 85078000                                                               |
| <b>Design</b>                   |                          |                                   |                                                                        |
| Form factor *                   | Rackmount                |                                   |                                                                        |
| Rack capacity                   | 2U                       |                                   |                                                                        |

**Logistics data**


Total carbon footprint (kg of CO2e) 3327.3

**Other features**

Output voltage 230 V



0731304327691



731304327691

### Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.