



FSP VIC GD 750W Power supply unit ATX ATX3.1 Black

Brand : FSP

Product code: POA7500101

Product name : VIC GD 750W Power supply unit ATX ATX3.1 Black

- Complies with ATX12V V3.1 & EPS 12V V2.92
 - Supports the latest PCIe 12V-2x6 connector (850W / 750W)
 - 80 PLUS® Gold certified
 - Efficiency $\geq 90\%$ at typical load
 - Active PFC, Power Factor ≥ 0.9
 - Low-loss LLC resonant-converter topology with synchronous Rectifier
 - Ultra-quiet and durable 120mm HDB fan
 - Durable 105°C bulk capacitor
 - High-power single +12V rail
 - Stable and efficient DC to DC module design
 - Premium embossed cables for easy routing
 - Complete Protections: OCP, OVP, SCP, OPP, UVP, OTP, SIP, NLO
 - Meet ErP/EuP 2013 standard
- VIC GD 750W Power supply unit ATX ATX3.1 Black



Power		Ports & interfaces	
Total power *	750 W	PCI Express power connectors (6+2 pin)	2
AC input voltage *	100 - 240 V	PCI Express power connectors (12-pin)	1
AC input frequency	50/60 Hz	PCI Express power cable length	60 cm
Input current	10 - 5 A	CPU power connector (4+4 pin)	✓
Power factor	0.9	CPU power cable length	80 cm
Power Factor Correction (PFC) type	Active	PCI Express connector	✓
Combined power (+3.3V)	80 W	Cabling type	Non-Modular
Combined power (+12V)	750 W	Performance	
Combined power (+5V)	80 W	80 PLUS certification *	80 PLUS Gold
Combined power (-12V)	3.6 W	Purpose *	PC
Combined power (+5Vsb)	15 W	Power supply unit (PSU) form factor *	ATX
Max output current (+3.3V)	16 A	ATX version	3.1
Max output current (+12V)	62.5 A	EPS version	2.92
Max output current (+5V)	16 A	Bearing technology	HDB
Max output current (-12V)	0.3 A	Design	
Max output current (+5Vsb)	3 A	Product colour	Black
Efficiency	90%	Cooling type	Active
Power protection features	Over voltage, Over current, Short circuit, Over power, Under voltage, Overheating, Surge & inrush, Surge & inrush protection (SIP), Surge and inrush, No load operation	Fan diameter	12 cm
Ports & interfaces		Number of fans	1 fan(s)
Motherboard power connector *	20+4 pin ATX	On/off switch	✓
Motherboard power cable length	50 cm	Weight & dimensions	
Number of SATA power connectors	5	Width	150 mm
SATA power cable length	450,600,750,900 mm	Depth	140 mm
Number of SATA power cables	2	Height	86 mm
Peripheral (Molex) power connectors (4-pin) *	3		

Ports & interfaces		Logistics data	
Peripheral (Molex) power cable length	600,750,900 mm	Warranty period	3 year(s)



4711498482105

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.