

Chieftec Core BBS-500S блок питания 500 W 24-pin ATX PS/2 Черный

Производитель : Chieftec **Семейство продуктов:** Core **Код товара:** BBS-500S

Модель : BBS-500S

Chieftec Core BBS-500S. Общая мощность: 500 W, Входящее напряжение сети: 100 - 240 V, Частота входящего переменного тока: 47 - 63 Hz. Разъем питания материнской платы: 24-pin ATX, Длина кабеля питания SATA: 150,500 mm, Длина периферийного (Molex) кабеля питания: 150,500 mm. Предназначение: ПК, Форм-фактор блока питания (БП): PS/2, 80 PLUS сертификация: 80 PLUS Gold. Цвет товара: Черный, Тип охлаждения: Активный, Диаметр вентилятора: 12 cm. Ширина: 140 mm, Глубина: 150 mm, Высота: 86 mm



Энергопитание		Порты и интерфейсы	
Общая мощность *	500 W	Количество 6+2 контактных разъёмов для питания PCI Express	1
Входящее напряжение сети *	100 - 240 V	Длина кабеля для питания PCI Express	50 cm
Частота входящего переменного тока	47 - 63 Hz	Разъем питания процессора (4+4-конт.)	✓
Ток на входе	8 A	Длина кабеля питания процессора	65 cm
Тип коррекции коэффициента мощности (PFC)	Активный	Разъем питания флоппи-дисков	1
Комбинированная мощность (-12 V)	3,6 W	Порт для флоппи-дисков	✓
Комбинированная мощность (+5 VSB)	12,5 W	Тип свивки	Немодульный
Максимальный выходной ток (+3.3 V)	18 A	Производительность	
Максимальный выходной ток (+12 V1)	41 A	80 PLUS сертификация *	80 PLUS Gold
Максимальный выходной ток (+5 V)	18 A	Предназначение *	ПК
Максимальный выходной ток (-12 V)	0,3 A	Форм-фактор блока питания (БП) *	PS/2
Максимальный выходной ток (+5 VSB)	2,5 A	Версия ATX	2.3
Функции защиты электропитания	Перенапряжение, Перегрузка, Короткое замыкание	Дизайн	
Порты и интерфейсы		Цвет товара	Черный
Разъем питания материнской платы *	24-pin ATX	Тип охлаждения	Активный
Количество разъемов питания SATA	4	Диаметр вентилятора	12 cm
Длина кабеля питания SATA	150,500 mm	Количество вентиляторов	1 вентилятор(ы)
Периферийные (Molex) разъемы питания (4-конт) *	3	Вес и размеры	
		Ширина	140 mm
		Глубина	150 mm
		Высота	86 mm
		Вес	1,65 kg

Порты и интерфейсы		Данные об упаковке	
Длина периферийного (Molex) кабеля питания	150,500 mm	Масса брутто	2,06 kg
Логистические данные			
Код гармонизированной системы описания (HS)		84733020	



0753263076120



753263076120

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.