



APC Smart-UPS SMT3000RMI2UC- 8x C13, 1x C19, USB, Rackmount 2U, SmartConnect, 3000VA

Brand : APC

Product code: SMT3000RMI2UC

Product name : APC Smart-UPS SMT3000RMI2UC- 8x C13, 1x C19, USB, Rackmount 2U, SmartConnect, 3000VA



- Intelligent and efficient network power protection from entry level to scalable runtime. Ideal UPS for servers, point-of-sale, routers, switches, hubs and other network devices
- Includes: CD with software, Documentation CD, Rack mounting hardware, Rack Mounting support rails, USB cable

APC Smart-UPS SMT3000RMI2UC- 8x C13, 1x C19, USB, Rackmount 2U, SmartConnect, 3000VA

APC Smart-UPS SMT3000RMI2UC- 8x C13, 1x C19, USB, Rackmount 2U, SmartConnect, 3000VA. UPS topology: Line-Interactive, Output power capacity: 3 kVA, Output power: 2700 W. AC outlet types: C13 coupler, C19 coupler, Power plug: C20 coupler, AC outlets quantity: 9 AC outlet(s). Battery technology: Sealed Lead Acid (VRLA), Battery capacity: 547 VAh, Typical backup time at full load: 3.2 min. Form factor: Rackmount, Product colour: Black, Rack capacity: 2U. Compliance certificates: RoHS, Certification: CE, EAC, EN 60950, EN/IEC 62040-1, EN/IEC 62040-2, GS Mark, IRAM, RCM, VDE, WEEE, REACH, PEP, EOL




Features		Design	
UPS topology *	Line-Interactive	Form factor *	Rackmount
Output power capacity *	3 kVA	Rack capacity	2U
Output power *	2700 W	Cable length	2 m
Waveform *	Sine	Product colour *	Black
Input operation voltage (min) *	151 V	Display type	LCD
Input operation voltage (max) *	302 V	LED indicators	Status
Input frequency *	50/60 Hz	Operational conditions	
Output operation voltage (min)	220 V	Operating temperature (T-T)	0 - 40 °C
Output operation voltage (max)	240 V	Storage temperature (T-T)	-15 - 45 °C
Automatic Voltage Regulation (AVR)	✓	Operating relative humidity (H-H)	0 - 95%
Surge energy rating	320 J	Storage relative humidity (H-H)	0 - 95%
Hold time (min)	4 ms	Operating altitude	0 - 3000 m
Hold time (max)	8 ms	Non-operating altitude	0 - 15000 m
Efficiency	98.9%	Certificates	
Noise level	55 dB	Compliance certificates	RoHS
Audible alarm(s)	✓	Certification	CE, EAC, EN 60950, EN/IEC 62040-1, EN/IEC 62040-2, GS Mark, IRAM, RCM, VDE, WEEE, REACH, PEP, EOL
Auto-restart	✓	Packaging content	
Ports & interfaces		Rack mount kit	✓
AC outlet types	C13 coupler, C19 coupler	Cables included	RS-232, USB cable
Power plug	C20 coupler	Management card included	✗
AC outlets quantity	9 AC outlet(s)	Quick installation guide	✓
Number of output IEC jumpers	3	Sustainability	
USB port	✓	Sustainability certificates	Green Premium
Serial interface	✓	Weight & dimensions	
Serial interface type	RJ-45	Width	432 mm
Ethernet LAN (RJ-45) ports	1		
SmartSlot	✓		
SmartConnect port	✓		

Battery		Weight & dimensions	
Battery technology	Sealed Lead Acid (VRLA)	Depth	683 mm
Battery capacity	547 VAh	Height	86 mm
Typical backup time at full load	3.2 min	Weight	44.3 kg
Typical backup time at half load	11.5 min	Packaging data	
Battery life (max)	5 year(s)	Software CD	✓
Battery recharge time	3 h	Bundled software	Powershute Business Edition
Hot-swap battery	✓	Package width	600 mm
Automatic battery test	✓	Package depth	980 mm
Cold start	✓	Package height	254 mm
		Package weight	51.7 kg
		Logistics data	
		Harmonized System (HS) code	85078000
		Total carbon footprint (kg of CO2e)	2968.55
		Other features	
		Nominal output voltage	230 V
		Nominal input voltage	230 V



0731304337348



731304337348

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.