



Canon EOS RP MILC Body 26.2 MP CMOS 6240 x 4160 pixels Black

Brand : Canon

Product family: EOS

Product code: 3380C003

Product name : RP

Canon EOS RP. Camera type: MILC Body, Megapixel (approx.): 26.2 MP, Sensor type: CMOS, Maximum image resolution: 6240 x 4160 pixels. ISO sensitivity (max): 40000. Digital zoom: 10x, Focal length range: 1 mm. Wi-Fi. HD type: 4K Ultra HD, Maximum video resolution: 3840 x 2160 pixels. Display diagonal: 7.62 cm (3"), Touchscreen. PictBridge. Weight: 440 g. Product colour: Black



Picture quality		Network	
Camera type *	MILC Body	Near Field Communication (NFC) * ✗	
Megapixel (approx.) *	26.2 MP		
Sensor type *	CMOS	Camera	
Maximum image resolution *	6240 x 4160 pixels	White balance *	Cloudy, Custom modes, Daylight, Flash, Fluorescent, Manual, Tungsten
Still image resolution(s) *	3:2 ratio (L, RAW, C-Raw) 6240x4160, (M1) 4160x2768, (S1) 3120x2080, (S2) 2400x1600 1.6x (crop) (L) 3888x2592, (S2) 2400x1600 4:3 ratio (L) 5536x4160, (M1) 3680x2768, (S1) 2768x2080, (S2) 2112x1600 16:9 ratio (L) 6240x3504, (M1) 4160x2336, (S1) 3120x1752, (S2) 2400x1344 1:1 ratio (L) 4160x4160, (M1) 2768x2768, (S1) 2080x2080, (S2) 1600x1600	Scene modes *	Children, Close-up (macro), Night, Night landscape, Night portrait, Panorama, Sports, Sunset, Twilight
		Shooting modes *	Aperture priority, Auto, Manual, Program, Shutter priority
		Photo effects *	Black&White, Grey, Neutral, Vivid
		Self-timer delay *	2,10 s
Image stabilizer *	✓	Contrast adjustment	✓
Supported aspect ratios	1:1, 2:3, 3:2, 3:4, 4:3, 16:9	Brightness adjustment	✓
Total megapixels	27.1 MP	Playback zoom (max)	10x
Image sensor size (W x H)	35.9 x 24 mm	Histogram	✓
Sensor format	Full-frame	Live view	✓
Image formats supported *	JPEG, Raw	On Screen Display (OSD) languages	
Lens system		BEL, Simplified Chinese, Traditional Chinese, Croatian, Czech, Danish, German, Dutch, English, Spanish, Finnish, Greek, Hungarian, Italian, Japanese, Korean, Norwegian, Swedish, Thai, Turkish, Ukrainian	
Digital zoom *	10x	Camera file system	Raw
Focal length range	1 mm	Multi-shot	✓
Focusing		Tripod mounting supported *	✓
Focus adjustment *	Auto/Manual	Built-in processor	✓
Auto focusing (AF) modes *	Contrast Detection Auto Focus, Multi Point Auto Focus, Single Auto Focus	Image processor	DIGIC 8
Auto Focus (AF) object detection	Face	Windows operating systems supported	Windows 10, Windows 10 Pro, Windows 10 x64, Windows 7, Windows 8.1
Face tracking	✓	Design	
Auto Focus (AF) points	4779	Product colour *	Black
Auto Focus (AF) points selection	Auto, Manual	Dustproof	✓
Auto Focus (AF) lock	✓	Splash proof	✓

Exposure		Design	
ISO sensitivity (min) *	100	Material	Fiberglass, Polycarbonate (PC)
ISO sensitivity (max) *	40000	Battery	
ISO sensitivity	100, 40000	Battery technology *	Lithium-Ion (Li-Ion)
Light exposure modes *	Aperture priority AE, Auto, Manual, Shutter priority AE	Battery voltage	7.2 V
Light exposure control	Program AE	Battery life (CIPA standard)	250 shots
Light exposure correction *	± 3EV (1/2EV; 1/3EV step)	Battery capacity	1040 mAh
Light metering *	Centre-weighted, Evaluative (Multi-pattern), Highlight-weighted, Spot	Number of batteries supported	1
Auto Exposure (AE) lock	✓	Rechargeable battery	✓
Number of measurement zones	384	Battery level indicator	✓
Shutter		Power	
Fastest camera shutter speed *	1/4000 s	USB Type-C charging port *	✓
Slowest camera shutter speed *	0.00025 s	USB Type-C required charging power (min) *	7.5 W
Camera shutter type	Electronic	USB Type-C required charging power (max) *	7.5 W
Flash		System requirements	
Flash modes *	Auto, Flash off, Flash on, High-speed synchronization, Manual, Normal, Red-eye reduction, Second curtain synchro, Slave	Mac compatibility	✓
Flash exposure lock	✓	Operational conditions	
Flash exposure compensation	✓	Recommended humidity operating range	0 - 85%
Flash exposure correction	±3EV (1/2; 1/3 EV step)	Maximum operating temperature range (T-T)	0 - 40 °C
Pre-flash	✓	Recommended operating temperature range (T-T)	0 - 40 °C
Shoe mounting point	✗	Operating temperature (T-T)	0 - 40 °C
Video		Storage temperature (T-T)	0 - 40 °C
Video recording *	✓	Operating relative humidity (H-H)	0 - 85%
Maximum video resolution *	3840 x 2160 pixels	Storage relative humidity (H-H)	0 - 85%
HD type *	4K Ultra HD	Weight & dimensions	
Video resolutions	1280 x 720,1920 x 1080,3840 x 2160	Width	132.5 mm
Video recording time	30 min	Depth	70 mm
Motion JPEG frame rate	60 fps	Height	85 mm
Resolution at capture speed	3840x2160@25fps	Weight	440 g
Video formats supported	MPEG4	Weight (including battery)	485 g
Audio		Packaging data	
Built-in microphone *	✓	Package width	282 mm
Audio system	stereo	Package depth	225 mm
Memory		Package height	151 mm
Compatible memory cards *	SDHC, SDXC	Package weight	1.22 kg
Memory slots	1	Packaging content	
Display		Neck strap included	✓
Display *	LCD	Shoulder strap	✓
Touchscreen *	✓	Power cord included	✓
Display diagonal *	7.62 cm (3")	AC adapter included *	✓
Display diagonal (metric)	7.5 cm	Battery charger included	✓
Display resolution	1040000 dot	Batteries included	✓
Flip-out screen	✓	Lens cap included	✓
Vari-angle LCD display	✓	Camera flash included	✓
Field of view	100%	User guide	✓
Viewfinder		Other features	
Viewfinder type	Electronic	Dimensions (WxDxH)	133 x 85 x 70 mm
Magnification	0.7x	Built-in flash	✓
Viewfinder screen size	0.39"	Aperture priority AE	✓
Viewfinder resolution (approx.)	236000 pixels	Auto exposure	✓
Ports & interfaces		Battery pack	✓

Ports & interfaces		Other features	
Connection to PC	✓	Display tilting	✓
PictBridge *	✓	Number of HDMI outputs	1
USB version *	2.0	Shutter priority AE	✓
USB connector	USB Type-C	USB 2.0 connectors	1
HDMI *	✓	Video compression formats	MPEG4
Microphone in	✓	Supplied battery type	LP-E17
USB port	✓	Technical details	
Network		Display brightness control	✓
Bluetooth *	✓	Batteries	LP-E17
Wi-Fi *	✓	Package weight	1.22 kg
Wi-Fi standards	802.11b, 802.11g, Wi-Fi 4 (802.11n)		



4549292132151

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.