



TP-Link TL-SG105-M2 сетевой коммутатор Неуправляемый 2.5G Ethernet (100/1000/2500) Черный

Производитель : TP-Link

Код товара: TL-SG105-M2

Модель : TL-SG105-M2



TP-Link TL-SG105-M2. Тип свича: Неуправляемый. Тип RJ-45 Ethernet портов для основного подключения: 2.5G Ethernet (100/1000/2500), Количество RJ-45 Ethernet портов для основного подключения: 5. Размер адресной таблицы: 16000 записей, Коммутационная способность: 25 Gbit/s. Стандарты сети: IEEE 802.3, IEEE 802.3ab, IEEE 802.3p, IEEE 802.3u, IEEE 802.3x, IEEE 802.3z



Характеристики управления		Энергопитание	
Тип свича *	Неуправляемый	Максимальное потребление энергии	12,11 W
Порты и интерфейсы		Power over Ethernet (PoE)	
Количество RJ-45 Ethernet портов для основного подключения *	5	Питание по Ethernet (PoE) *	✗
Тип RJ-45 Ethernet портов для основного подключения *	2.5G Ethernet (100/1000/2500)	Условия эксплуатации	
Количество портов 2,5G Ethernet (медь)	5	Диапазон температур при эксплуатации	0 - 40 °C
Сеть		Диапазон температур при хранении	-40 - 70 °C
Стандарты сети *	IEEE 802.3, IEEE 802.3ab, IEEE 802.3p, IEEE 802.3u, IEEE 802.3x, IEEE 802.3z	Диапазон относительной влажности при эксплуатации	10 - 90%
Поддержка 10G *	✗	Диапазон относительной влажности при хранении	5 - 90%
Авто MDI/MDI-X	✓	Тепловыделение	41,32 BTU/ч
Скорость передачи данных Ethernet LAN	10,100,1000 Мбит/с	Вес и размеры	
Автоматическое согласование	✓	Ширина	209 mm
Передача данных		Глубина	126 mm
Коммутационная способность *	25 Gbit/s	Высота	26 mm
Скорость передачи	18,6 Mpps	Содержимое упаковки	
Размер адресной таблицы *	16000 записей	Поставляемые кабели	LAN (RJ-45)
Промежуточное хранение	✓	Краткая инструкция пользователя	✓
Поддержка Jumbo Frames	✓	Данные об упаковке	
джамбо кадры	10000	Ширина упаковки	240 mm
Пакетная буферная память	1,5 MB	Глубина упаковки	315 mm
Дизайн		Высота упаковки	70 mm
Монтаж в стойку *	✗	Масса брутто	920 g
Цвет товара	Черный		

Дизайн		Сертификаты	
Светодиодные индикаторы	✓	Сертификация	CE, FCC ,RoHS
Энергопитание		Логистические данные	
Источник питания *	Постоянный ток	Код гармонизированной системы описания (HS)	85176990
Блок питания в комплекте *	✓		
Ток на входе	1 A		
Входное напряжение	12 V		



6935364052898




6935364052881



0845973089757



845973089757



1210002612654



1210002612661

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.