



# D-Link DGS-105GL Nepārvaldīts Gigabit Ethernet (10/100/1000) Desktops Melns

**Zīmols :** D-Link

**Preces kods:** DGS-105GL/B

**Modeļa nosaukums :** DGS-105GL



D-Link DGS-105GL. Slēdža tips: Nepārvaldīts. Basic switching RJ-45 Ethernet portu veids: Gigabit Ethernet (10/100/1000), Basic switching RJ-45 Ethernet portu daudzums: 5. Adrešu tabulas izmērs: 2000 ieraksti, Komutācijas ietilpība: 10 Gbit/s. Tīkla standarts: IEEE 802.1p, IEEE 802.3, IEEE 802.3ab, IEEE 802.3az, IEEE 802.3u, IEEE 802.3x. DC ievades spriegums: 5 V. Formas faktors: Desktops

| Vadības īpašības                                |                                                                               | Dizains                                   |                         |
|-------------------------------------------------|-------------------------------------------------------------------------------|-------------------------------------------|-------------------------|
| Slēdža tips *                                   | Nepārvaldīts                                                                  | Produkta krāsa                            | Melns                   |
| Quality of Service (QoS) atbalsts               | ✓                                                                             | Apvalka materiāls                         | Metāls                  |
| Savienojamība                                   |                                                                               | LED indikatori                            | Aktivitāte, Link, Jauda |
| Basic switching RJ-45 Ethernet portu daudzums * | 5                                                                             | Darbības rādītāji                         |                         |
| Basic switching RJ-45 Ethernet portu veids *    | Gigabit Ethernet (10/100/1000)                                                | Vidējais laiks starp kļūmēm (MTBF)        | 1455562 h               |
| Tīklošana                                       |                                                                               | Energijas pārvaldība                      |                         |
| Tīkla standarts *                               | IEEE 802.1p, IEEE 802.3, IEEE 802.3ab, IEEE 802.3az, IEEE 802.3u, IEEE 802.3x | Jaudas avots *                            | Līdzstrāvas             |
| Vara Ethernet kabeļu tehnoloģija                | 10BASE-T, 100BASE-TX, 1000BASE-T                                              | DC ievades spriegums                      | 5 V                     |
| Plūsmas kontroles atbalsts                      | ✓                                                                             | Ieejas strāva                             | 1 A                     |
| Auto MDI/MDI-X                                  | ✓                                                                             | Strāvas patēriņš (maks)                   | 3,55 W                  |
| Datu pārraide                                   |                                                                               | Ārējās vides apstākļi                     |                         |
| Komutācijas ietilpība *                         | 10 Gbit/s                                                                     | Darbības temperatūras amplitūda (T-T)     | 0 - 40 °C               |
| Pakešu apstrādes jauda                          | 7,44 miljons pakešu sekundē                                                   | Uzglabāšanas temperatūras amplitūda (T-T) | -10 - 70 °C             |
| Adrešu tabulas izmērs *                         | 2000 ieraksti                                                                 | Darbības relatīvā mitruma amplitūda       | 10 - 90%                |
| Uzglabāt un pārsūtīt                            | ✓                                                                             | Uzglabāšanas relatīvā mitruma amplitūda   | 5 - 95%                 |
| Rindu skaits                                    | 8                                                                             | Karstuma izkliedēšana                     | 12,11 BTU/h             |
| Jumbo Frames atbalsts                           | ✓                                                                             | Svars&dimensijas                          |                         |
| Jumbo rāmji                                     | 9216                                                                          | Platums                                   | 100 mm                  |
| Pakešu nosūtīšanas ātrums (1 Gbps)              | 1488000 Paketes sekundē                                                       | Dziļums                                   | 64 mm                   |
| Pakešu nosūtīšanas ātrums (100 Mbps)            | 148800 Paketes sekundē                                                        | Augstums                                  | 24 mm                   |
| Pakešu nosūtīšanas ātrums (10 Mbps)             | 14880 Paketes sekundē                                                         | Svars                                     | 160 g                   |
| Dizains                                         |                                                                               | Sertifikāti                               |                         |
| Sakraujams *                                    | ✓                                                                             | Atbilstības sertifikāti                   | CE, RoHS                |
| Formas faktors                                  | Desktops                                                                      | Sertifikācija                             | CE; FCC; RoHS           |
|                                                 |                                                                               | Logistiskie dati                          |                         |
|                                                 |                                                                               | Harmonizētās sistēmas (HS) kods           | 85176990                |



0790069458606



790069458606

### Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.