



Dahua Technology PFS3009-8ET-96 Unmanaged L2 Fast Ethernet (10/100) Power over Ethernet (PoE) Black

Brand : Dahua Technology

Product code: PFS3009-8ET1GT-96

Product name : PFS3009-8ET-96

- Layer two commercial switch
- > Supports PoE power management
- > Supports wall-mount installation
- > Supports anti-theft lock hole
- > MAC auto learning and aging, MAC address capacity is 2K
- > Supports IEEE802.3, IEEE802.3u and IEEE802.3X standards
- > RJ45 port supports 10/100 Mbps self-adaptation
- > Supports 250 meters long distance PoE transmission
- > Conforms to IEEE802.3af and IEEE802.3at power supply standard. Port 1 supports Hi-PoE 60W power supply

1.8Gbps, 1.34Mpps, 768Kb, 2K, 5%~95%, DC 48~57V, 4KV, 2KV, 8KV, -10°C~55°C, 490g, 190mm×100mm×30mm

Dahua Technology PFS3009-8ET-96 Unmanaged L2 Fast Ethernet (10/100) Power over Ethernet (PoE) Black:

DH-PFS3009-8ET-96 is an 8-port fast ethernet switch, which supports 250 meters long distance PoE transmission. It provides 8*10/100Mbps PoE ports and 1*100 Mbps uplink port. The product is equipped with two transmission modes (Default/Extend), which are controlled by DIP switch.

Management features		Design	
Switch type *	Unmanaged	Rack mounting *	✗
Switch layer	L2	Stackable *	✗
Ports & interfaces		Product colour	Black
Basic switching RJ-45 Ethernet ports quantity *	8	Power	
Basic switching RJ-45 Ethernet ports type *	Fast Ethernet (10/100)	DC input voltage	48 - 57 V
Network		Power over Ethernet (PoE)	
Networking standards *	IEEE 802.3af, IEEE 802.3at	Power over Ethernet (PoE) *	✓
10G support *	✗	Power over Ethernet (PoE) ports quantity	8
Flow control support	✓	Total Power over Ethernet (PoE) budget	96 W
Auto MDI/MDI-X	✓	Operational conditions	
MAC address auto-learning supported	✓	Operating temperature (T-T)	-10 - 55 °C
MAC address auto-aging supported	✓	Operating relative humidity (H-H)	10 - 90%
Data transmission		Weight & dimensions	
Switching capacity *	1.8 Gbit/s	Width	190 mm
Forwarding rate	1.34 Mpps	Depth	100 mm
MAC address table *	2000 entries	Height	30 mm
Packet buffer memory	0.768 MB	Weight	480 g

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.