

CyberPower PDU24005 energosadales vienība, PDU 10 Maiņstrāvas izvade (-s) 1U Melns

Zīmols : CyberPower

Preces kods: PDU24005

Modeļa nosaukums : PDU24005

CyberPower PDU24005. PDU veidi: Mērāms, Statņa kapacitāte: 1U, Tips: Vienfāzes. Izeju skaits: 10 Maiņstrāvas izvade (-s), Maiņstrāvas izeju tipi: C13 uzmava, C19 uzmava, Jaudas spraudnis: C20 uzmava. LED indikatori: Link, Status, Kabeļa garums: 3,05 m. Nominālais ieejas spriegums: 200 - 240 V, Maksimālā strāva: 12 A, Maiņstrāvas ievades frekvence: 50 / 60 Hz. Atbilstības sertifikāti: CB, CE, Federālā komunikāciju komisija, RoHS, UL, Sertifikācija: FCC Class A, UL62368, EN 55032 Class A, IEC 62368



Dizains		Sertifikāti	
PDU veidi *	Mērāms	Atbilstības sertifikāti	CB, CE, Federālā komunikāciju komisija, RoHS, UL
Tips	Vienfāzes	Sertifikācija	FCC Class A, UL62368, EN 55032 Class A, IEC 62368
Statņa kapacitāte *	1U	Ilgspēja	
Montāža	Horizontāls	Ilgspējas atbilstība	✓
Apvalka materiāls	Tērauds	Ārējās vides apstākļi	
Produkta krāsa	Melns	Darbības temperatūras amplitūda (T-T)	0 - 45 °C
Ekrāns	LCD	Uzglabāšanas temperatūras amplitūda (T-T)	-15 - 95 °C
Savienojamība		Darbības relatīvā mitruma amplitūda	0 - 95%
Izeju skaits *	10 Maiņstrāvas izvade (-s)	Uzglabāšanas relatīvā mitruma amplitūda	0 - 95%
Jaudas spraudnis	C20 uzmava	Ekspluatācijas augstums	0 - 4000 m
Maiņstrāvas izeju tipi *	C13 uzmava, C19 uzmava	Ne-operacionālais augstums	0 - 15000 m
Seriaļo pieslēgvietu skaits	1	Darbības temperatūras amplitūda (T-T)	32 - 113 °F
Ethernet LAN (RJ-45) pieslēgvietu skaits	1	Svars&dimensijas	
USB pieslēgvietu skaits	1	Platums	433 mm
Īpašības		Dziļums	215 mm
LED indikatori	Link, Status	Augstums	44 mm
Kabeļa garums	3,05 m	Svars	3,2 kg
Vadības īpašības		Informācija par iepakojumu	
Programmaparatūra atjauninājama	✓	Iepakojuma svars	6 kg
Energijas pārvaldība		Iepakojuma platums	550 mm
Nominālais ieejas spriegums *	200 - 240 V	Iepakojuma dziļums	398 mm
Maiņstrāvas ievades frekvence	50 / 60 Hz	Iepakojuma augstums	125 mm
Maksimālā strāva *	12 A		
Niminālais izejas spriegums	200 - 240 V		
Jaudas aizsardzības apraksts	Pārslodze		
Automātiskais izslēgšanas slēdzis	✓		

Logistiskie dati

Garantijas periods

2 gads(i)



4711027799797



0649532933358



649532933358

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.